

HT23-401

NEMA 23 High Torque *tep* Motor



Product Features

- 2-phase hybrid step motor
- High torque design
- Standard NEMA 23 dimensions
- Series or parallel wiring



Description





The HT23-401 two-phase stepper motor is suitable for a wide range of motion control applications. Terminated with 8 motor leads, the motor can be connected in a few different ways, including bipolar series and bipolar parallel.

Specifications

Part Number	HT23-401
Frame Size	NEMA 23
Motor Type	High torque
Part Number w/Double Shaft	NA
Part Number w/Encoder	HT23-401D-ZAA
Motor Length	2.99 inches
Number of Lead Wires	8
Lead Wire Configuration	flying leads, no connector
Lead Wire/Cable Length	18 inches
Lead Wire Gauge	22 AWG
Unipolar Holding Torque	187 oz-in
Bipolar Holding Torque	264 oz-in
Step Angle	1.8 deg
Bipolar Series Current	2.12 A/phase
Bipolar Series Resistance	2.0 Ohms/phase

Bipolar Series Inductance	6.4 mH/phase
Bipolar Parallel Current	4.24 A/phase
Bipolar Parallel Resistance	0.5 Ohms/phase
Bipolar Parallel Inductance	1.6 mH/phase
Unipolar Current	3.00 A/phase
Unipolar Resistance	1.0 Ohms/phase
Unipolar Inductance	1.6 mH/phase
Rotor Inertia	6.80E-03 oz-in-sec ²
Integral Gearhead	No
Weight	2.2 lbs
Storage Temperature	-40 to 70 °C
Operating Temperature	-20 to 50 °C
Insulation Class	Class B (130 °C)
Maximum Radial Load	NA
Maximum Thrust Load	NA
Shaft Run Out	0.002 inch T.I.R. max
Radial Play	0.001 inch max w/ 1.1 lb load
End Play	0.003 inch max w/ 2.2 lb load
Perpendicularity	0.003 inches
Concentricity	0.003 inches

Downloads

Datasheet	 StepMotorWiring-8-lead-striped.pdf
2D Drawing	 HT23-401_RevE.pdf
3D Drawing	 23HT76D.igs
Speed-Torque Curves	 ST_speed-torque.pdf
Agency Approvals	There are no related agency approval documents at this time.
Application Notes	There are currently no Application Notes available for this product.