Immersion


ARMT-1

Clean Water **Applications**


- 1-1/4" NPT Brass Screw Plug
- Copper Sheath Elements
- High Watt Density (43 86 W/In²)
- 1 2 kW
- Integral Thermostat (SPST)
- 120 and 240 Volt, Single Phase
- General Purpose or Moisture **Resistant/Explosion Resistant Terminal Enclosure**



E1 — Dimensions (Inches)







(2) 1-1/4" NPT Conduit Hubs (one side plugged) -

Same-day shipping on stock item orders received before 4 pm CST 3-day shipping on assembly-stock ite

Specifications and Ordering Information

							T4 — Temperature (60 - 187°F)			T5 — Temperature (60 - 240°F)			T8 — Temperature (0 - 127°F)		
kW		Phase	•	No. Elem.	DIM B (In.)	Wt. (Lbs.)	Model	Stock	PCN	Model	Stock	PCN	Model	Stock	PCN
1 1	120 240	ral Pur 1 1	pose ¹ 43 43	2 2	6-1/8 6-1/8	5 5	ARMT-110-3T4 ARMT-110-3T4	AS AS	036564 036572	ARMT-110-3T5 ARMT-110-3T5	AS AS		ARMT-110-3T8 ARMT-110-3T8	AS AS	036724 036732
1.2 1.2	120 240	1	53 53	2 2	6-1/8 6-1/8	5 5	ARMT-112T4 ARMT-112T4	AS AS	036580 036599		AS AS	036660	ARMT-112T8 ARMT-112T8	AS AS	036740 036759
1.5 1.5	120 240	1 1	65 65	2	6-1/8 6-1/8	5 5	ARMT-115T4 ARMT-115T4	AS AS	036601 036610		AS AS	036695	ARMT-115T8	AS AS	036767 036775
2	120 240	1	86 86	2	6-1/8	5 5	ARMT-120T4 ARMT-120T4	AS AS		ARMT-120T5 ARMT-120T5	AS AS		ARMT-120T8 ARMT-120T8	AS AS	036783 036791
E2 Moisture Resistant/Explosion Resistant²															
1	120 240	1 1	43 43	2 2	6-1/8 6-1/8	8 8	ARMT-110-3E2T4 ARMT-110-3E2T4	AS AS		ARMT-110-3E2T5 ARMT-110-3E2T5	AS AS		ARMT-110-3E2T8 ARMT-110-3E2T8	AS AS	036960 036978
1.2 1.2	120 240	1 1	53 53	2	6-1/8 6-1/8	8 8	ARMT-112E2T4 ARMT-112E2T4	AS AS	036820 036839	ARMT-112E2T5 ARMT-112E2T5	AS AS		ARMT-112E2T8 ARMT-112E2T8	AS AS	036986 036994
1.5 1.5	120 240	1	65 65	2 2	6-1/8 6-1/8	8 8	ARMT-115E2T4 ARMT-115E2T4	AS AS	036847 036855	ARMT-115E2T5 ARMT-115E2T5	AS AS		ARMT-115E2T8 ARMT-115E2T8	AS AS	037006 037014
2 2	120 240	1 1	86 86	2 2	6-1/8 6-1/8	8 8	ARMT-120E2T4 ARMT-120E2T4	AS AS	036863 036871	ARMT-120E2T5 ARMT-120E2T5	AS AS		ARMT-120E2T8 ARMT-120E2T8	AS AS	037022 037030

 $\begin{array}{lll} \textbf{Stock Status:} & \textbf{S} = \text{stock} & \text{AS} = \text{assembly stock} & \text{NS} = \text{non-stock} \\ \textbf{To Order} & \textbf{Specify model, volts, phase, kW, PCN and quantity.} \\ \end{array}$

- Heaters with General Purpose Enclosures are UL Listed and CSA Certified.
 Heaters with Moisture Resistant/Explosion Resistant Enclosures are CSA NRTL/C Certified.