

CD1H, CD2H Pressure Switch

Diaphragm

CD1H, CD2H Series



- ✦ High Reliability
- ✦ Extremely Versatile
- ✦ Calibrated Dial for Easy Set Point Adjustment
- ✦ Ideal for Pressure or Vacuum

Barksdale's CD1H and CD2H Housed Diaphragm Pressure

Switches provide an ideal solution for pressure control applications requiring tamper proof external adjustment and environments which require water-tight NEMA 4 housings. These pressure switches are available in single or dual control settings for both positive pressure and vacuum models, to 150 psi. These snap-action switches may be wired normally open or normally closed through a 3/4"-14 NPT conduit connector to free leads to 18". All models feature self-locking set screw adjustment and dials which are calibrated for increasing setting. For applications requiring a highly accurate switch in a durable package, **Barksdale's CD1H and CD2H Diaphragm Pressure Switches** are the ideal choice. Stripped models are also available.

CD1H, CD2H Pressure Switch

With Barksdale - Pressure's No Problem

As a recognized leader in the manufacture of pressure product solutions, Barksdale pressure switches meet the demanding needs of our customers. From 29" Hg to 18,000 psi, Barksdale has pressure switches for a variety of applications – from transformers to natural gas compressors to beverage dispensers – and more!

Barksdale's Diaphragm Pressure Switches provide an economical solution for your pressure sensing needs. Diaphragm switches accurately control pressures from 30 inches of mercury vacuum to 150 psi positive pressure, and can be factory pre-set upon request. Setpoint adjustment is easily accomplished by turning the adjustment screws, which are protected by a tamper-resistant cover on housed models. A variety of available factory options allows the Diaphragm switches to be configured to the exact needs of your application.

Diaphragm Pressure Switch Applications

With its economical design and high repeatability, **Barksdale's Diaphragm Pressure Switches** provide an accurate and reliable solution for pressures up to 150 psi, making them ideal for use in:

- Pump & Compressor Monitoring
- Air Proving in HVAC Systems
- Engine Monitoring
- Machine Tools
- Hydraulic Power Units



Need Something Special?

If you have special product requirements, we can help. Barksdale specializes in custom design solutions to meet your needs. Our reputation is built on creating custom products for customers committed to getting exactly what they need. We have design engineers and technical specialists who are experts in solving your unique pressure problems. Our technology and resources are at your disposal.

Need More Information?

Call us. We are only a phone call away.
Toll-Free: 1-800-835-1060.

CD1H, CD2H Pressure Switch

General Description

Electrical Characteristics

All models incorporate Underwriters' Laboratories, Inc. listed single pole double throw snap-action switching elements.

Performance Characteristics

Accuracy

+/- 0.5% of the adjustable range

Switch

Type

SPDT single or dual circuit

Rating

10 Amps @ 125/250 VAC, 3 Amps @ 480 VAC; .5 Amps @ 24 VDC (Class A or H Limit Switch); Consult sales drawing for ratings of optional Limit Switches

Physical

Weight

Approximate 1.75 lbs.

Enclosure/Housing

NEMA 4

Electrical Connection

Free leads approximately 18" long, 16 AWG through 3/4" NPT conduit connector.

Pressure Connection

1/4" NPT internal thread.

Diaphragm

17-7 PH stainless steel

Approvals/Listings

UL

All models are Underwriters' Laboratories listed in the Electrical Construction Materials Directory under Industrial Control Equipment. Float and Pressure Operated, File E42816, and Canadian Standards Association Listed under Guide 380-W-1.16, Class 3231, File 22355.

CSA

Listed under Guide 380-W-1.16, Class 3231, File 22355

Environmental

Temperature Range

Operating

-65° to +165°F (-54° to +74°C)

Storage

-65° to +200°F (-54° to +93°C)

WIRE CODE

Lead	Circuit #1		Circuit #2	
	Pressure	Vacuum	Pressure	Vacuum
Normally Closed	Blue	Red	Orange	Yellow
Common	Purple	Purple	Brown	Brown
Normally Open	Red	Blue	Yellow	Orange

Adjustment Instructions

Pressure

Turn self-locking adjustment screw counter clockwise to increase pressure setting


Vacuum

Turn self-locking adjustment screw clockwise to increase vacuum setting

Consult Factory for These Options

Cleaned for Oxygen Service


1/2" NPT Pressure Port



CD1H, CD2H Pressure Switch

Diaphragm

CD1H, CD2H Series



Example: CD1H-A3SS

Miscellaneous:	
Paper Tag	\$5.00
Metal Tag	\$10.00

Barksdale
CONTROL PRODUCTS

3211 Fruitland Avenue • Los Angeles, CA 90058 • ☎ 800-835-1060 • Fax: 323-589-3463 • www.barksdale.com

See Barksdale's Standard Conditions of Sale • Specifications are subject to modification at any time • Bulletin #S0079-A • 01/05 • ©2005 • Printed in the U.S.A.