

## 1015 recessed magnetic contact

recessed press fit magnetic contact with wire leads  
1/4 in. dia.

The 1015 magnetic contact is designed with a flat side on the surface of the contact, which allows a flush fit on narrow surfaces.

This contact is recommended for use with casement windows, awning windows, and other areas where the contact must recess and fit into a narrow surface. It installs quickly in a 1/4-inch diameter hole. Small fins on the housing of the magnet and switch eliminate the need for glue.



### Specifications

Voltage:	100 VAC/VDC max.
Current:	0.5 A max.
Power:	7.5 W max.
Loop type:	Closed
Electrical configuration:	Normally open
Gap distance:	Up to 3/8 in.
Lead type:	1 ft. #22 wire
Dimensions:	1.625 in. L x 0.25 in. dia. (33 x 6.4 mm) with a 3/8 in. dia. (9.5 mm) tapered head
Housing:	Flame retardant ABS plastic
Color:	White
Regulatory:	UL, CUL

### Ordering information

1015N-10PKG	Recessed contact with wire leads, 1/4 in. dia., 3/8 in. gap size, white, pk/10
-------------	--

- Press fit design makes installation easy no screws or glue needed
- Attractive, added security of recessed mounting
- Flat-sided head for use in limited spaces
- 1/4-inch diameter

