Immersion


EMTI-3

Severely Corrosive Solution Applications

- 2" NPT Stainless Steel **Screw Plug**
- INCOLOY® Sheath Elements
- Low Watt Density (15 W/In²)
- 1 6 kW
- Without Thermostat
- 240 and 480 Volt, Three Phase
- General Purpose or Moisture **Resistant/Explosion Resistant Terminal Enclosure**




E1 — Dimensions (Inches)





E2 — Dimensions (Inches)



3-day shipping on assembly-stock it

Specifications and Ordering Information

						E1 General Purpose ¹				E2 Moisture Resistant/Explosion Resistant ²			
kW	Volts	Phase	W/In²	No. Elem.	DIM B (In.)	Model	Stock	PCN	Wt. (Lbs.)	Model	Stock	PCN	Wt. (Lbs.)
1 1	240 480	3 3	15 15	3 3	7-3/4 7-3/4	EMTI-301 EMTI-301	AS AS	091440 091459	5 5	EMTI-301E2 EMTI-301E2	AS AS	033494 033507	8 8
2 2	240 480	3	15 15	3 3	17-3/4 17-3/4	EMTI-302 EMTI-302	AS AS	091467 091475	6 6	EMTI-302E2 EMTI-302E2	AS AS	033515 033523	9
3	240 480	3	15 15	3	24-7/8 24-7/8	EMTI-303 EMTI-303	AS AS	091483 091491	7 7	EMTI-303E2 EMTI-303E2	AS AS	033531 033540	10 10
4 4	240 480	3	15 15	3 3	32-7/16 32-7/16	EMTI-304 EMTI-304	AS AS	091504 091512	9	EMTI-304E2 EMTI-304E2	AS AS	033558 033566	12 12
5 5	240 480	3	15 15	3	40-3/8 40-3/8	EMTI-305 EMTI-305	AS AS	091520 091539	10 10	EMTI-305E2 EMTI-305E2	AS AS	033574 033582	13 13
6 6	240 480	3 3	15 15	3 3	47-7/8 47-7/8	EMTI-306 EMTI-306	AS AS	091547 091555	12 12	EMTI-306E2 EMTI-306E2	AS AS	033590 033603	15 15

- Heaters with General Purpose Enclosures are UL Listed and CSA Certified. Heaters with Moisture Resistant/Explosion Resistant Enclosures are CSA NRTL/C Certified.