

FiberFlo T Pleated Filters

Polytetrafluoroethylene (PTFE)

Pleated Cartridge Filters

FiberFlo PTFE cartridge filters provide microfilter users with reliable flow rates, chemical compatibility, economical filtration, and solvent compatibility. Containing 7.0 square feet of expanded PTFE membrane, FiberFlo PTFE Filters offer users a highly efficient hydrophobic “barrier”, ensuring low moisture content of ultrapure gasses. Additionally, it will ensure filtration performance in the purification of aggressive liquids and organic solvents. Each FiberFlo PTFE cartridge filter is manufactured under QSR; representative samples from each manufacturing lot are tested for integrity to ensure consistent performance.



Standard Features

- Reliable liquid flow rates
- Dependable air flow rates
- Broad chemical compatibility
- Broad range of pore size options
- Superior hydrophobicity
- Economical filtration

Applications

- Photoresists
- Compressed gas
- Electronic grade solvents
- Pharmaceutical and intermediate solvents
- Hot deionized water
- Tank vents

Flow Rates

The following table represents typical water flow at a one psi (69 mbar) pressure differential across a single 10-inch cartridge element. The test fluid is water at ambient temperature. Extrapolation for housings with multiple elements and higher pressure drops is acceptable, but as flows increase the pressure drop of the housing becomes more apparent.

Typical Flow Rate				
Pore Size	0.1 μm	0.22 μm	0.45 μm	1.0 μm
GPM	1.25	2.8	5.7	18.0
SCFM	> 26	> 42	> 68	> 85
Pore Size Rating (Gas)	0.01 μm	0.02 μm	0.05 μm	0.1 μm

Technical Data

FiberFlo PTFE Pleated Cartridge Specifications	
Materials of Construction	
Membrane:	PTFE
Support Layers:	Polypropylene
Cartridge Hardware:	Polypropylene
Maximum Operating Pressure	
Forward:	50 psi (3.4 bar) @ 68°F (20°C)
Reverse:	40 psi (2.7 bar) @ 68°F (20°C)
Chemical Compatibility	
Compatible with most semiconductor grade solvents and other chemicals.	

End Fitting Options:		
FiberFlo Codes	Description	Std. Reference
A	Single open-end, 222 o-ring, flat bottom	Code 3
B	Single open-end, 222 o-ring, with fin	Code 8
C	Single open-end, 226 o-ring, with fin	Code 7

Nomenclature Format - FPT-02-30-C						
FPT	-	02	-	30	-	C
FiberFlo	Micron Rating		Length		End Fitting Code	(See table above)
PTFE	005 - 0.05 µm		10 - 10 inch			
Pleated	01 - 0.1 µm		20 - 20 inch			
Cartidge	02 - 0.2 µm		30 - 30 inch			
	045 - 0.45 µm		40 - 40 inch			
	1 - 1.0 µm					



Mar Cor Purification 4450 Township Line Road Skippack, PA 19474-1429 Tel: (484) 991-0220 Toll Free: (800) 346-0365 Fax: (484) 991-0230	Mar Cor Purification 14550 28th Avenue North Plymouth, MN 55447 Tel: (484) 991-0220 Toll Free: (800) 633-3080 Fax: (763) 210-3868	Mar Cor Purification 3250 Harvester Road - Unit 6 Burlington, ON L7N 3W9 Tel: (905) 639-7025 Toll Free: (800) 268-5035 Fax: (905) 639-0425	Mar Cor Purification Sourethweg 11 6422 PC Heerlen The Netherlands Tel: (+31) 45 5471 471 Fax: (+31) 45 5429 695	Mar Cor Purification 1A International Business Park, #05-01 Singapore 609933 Tel: (+65) 6227 9698 Fax: (+65) 6225 6848
---	--	---	---	---