To give you the best possible experience, this site uses cookies. By continuing to use the site, or by staying here, you agree to our use of cookies in line with our Privacy Policy.	Learn more including
how to manage cookies here	

Accept

ISO 7241 SERIES B INTERCHANGE, MULTI-PURPOSE QUICK COUPLINGS (HYDRAULIC, FLUIDS, GAS, STEAM) UP TO 5000 PSI - 60 SERIES NIPPLES



60 series 316 stainless steel nipple, ISO 7241-1 series B

PART NUMBER: SSH4-63W	
MAXIMUM WORKING PRESSURE (PSI): 5000	
APPLICATION: General Purpose	
BODY SIZE (INCH): 1/2	
BODY MATERIAL: 316 Stainless steel	
CONNECTION THREAD SIZE (INCH): 1/2 - 14	
CONNECTION TYPE: NPTF	
SEAL MATERIAL: Ethylene propylene	
	Reset Attributes
	WHERE TO BUY
PRODUCT OVERVIEW	

Print Tech Specifications

TECH SPECIFICATIONS

PERFORMANCE CHARACTERISTICS

MAXIMUM WORKING PRESSURE (PSI)

5000
MAXIMUM WORKING PRESSURE (BAR)
340
FLOW RATE (GPM)
12
FLOW RATE (LPM)
45
MEDIA
Hydraulic
INDUSTRY STANDARDS
ISO 7241-1, series B
COUPLING HALF
Nipple
MINIMUM WORKING TEMPERATURE (F)
-65
MINIMUM WORKING TEMPERATURE (C)
-54
MAXIMUM WORKING TEMPERATURE (F)
400
MAXIMUM WORKING TEMPERATURE (C)
MAXIMUM WORKING TEMPERATURE (C) 204
` ,
204
204 VALVE STYLE
204 VALVE STYLE Poppet
204 VALVE STYLE Poppet VACUUM RATING (INCH OF HG)
204 VALVE STYLE Poppet VACUUM RATING (INCH OF HG) 27.4
204 VALVE STYLE Poppet VACUUM RATING (INCH OF HG) 27.4 VACUUM RATING (BAR)
204 VALVE STYLE Poppet VACUUM RATING (INCH OF HG) 27.4 VACUUM RATING (BAR) -0.9
204 VALVE STYLE Poppet VACUUM RATING (INCH OF HG) 27.4 VACUUM RATING (BAR) -0.9 THREAD STYLE
204 VALVE STYLE Poppet VACUUM RATING (INCH OF HG) 27.4 VACUUM RATING (BAR) -0.9 THREAD STYLE Female
204 VALVE STYLE Poppet VACUUM RATING (INCH OF HG) 27.4 VACUUM RATING (BAR) -0.9 THREAD STYLE Female PLATING
204 VALVE STYLE Poppet VACUUM RATING (INCH OF HG) 27.4 VACUUM RATING (BAR) -0.9 THREAD STYLE Female PLATING na
204 VALVE STYLE Poppet VACUUM RATING (INCH OF HG) 27.4 VACUUM RATING (BAR) -0.9 THREAD STYLE Female PLATING na VALVE MATERIALS
VALVE STYLE Poppet VACUUM RATING (INCH OF HG) 27.4 VACUUM RATING (BAR) -0.9 THREAD STYLE Female PLATING na VALVE MATERIALS 316 Stainless steel
VALVE STYLE Poppet VACUUM RATING (INCH OF HG) 27.4 VACUUM RATING (BAR) -0.9 THREAD STYLE Female PLATING na VALVE MATERIALS 316 Stainless steel

Based on your experience finding this product today, how likely are you to recommend Parker Hannifin to a friend or colleague?

Not at all likely Extremely likely

CAD

PRODUCT SUPPORT

RECOMMENDED



ISO 7241 series B Interchange, Multi-Purpose Quick Couplings (hydraulic,



and Plugs (Molded and Metal) for Quick Couplings



SNAP-TITE DESIGN, MULTI-PURPOSE QUICK COUPLINGS (HYD, FLUIDS) UP TO 11 000 PSI - H



SNAP-TITE DESIGN, MULTI-PURPOSE QUICK COUPLINGS (HYD, FLUIDS) UP TO

FOLLOW US

Follow Parker Hannifin on social media:













CONTACT US

Parker Hannifin Corporation

Quick Coupling Division 8145 Lewis Road Minneapolis, MN 55427 USA

Phone +1 (763) 544-7781 Fax

+1 (763) 544-3418

EMAIL PARKER

Parker Hannifin

Products About Parker Investors Community

Careers

Global Operations

Divisions Sales Companies Worldwide Locations **Distribution Network**

ParkerStore™ Network

Company Information

Newsroom

Working with Parker

Event Calendar Product Brands

History

Global Support Center

Support CAD

Where to Buy **Contact Parker**

Manage Online Orders

ENGINEERING YOUR SUCCESS.

SITE MAP | SAFETY | PRIVACY POLICIES TERMS AND CONDITIONS © PARKER HANNIFIN CORP 2019